2026 SAFETY INSPECTION AND REGISTRATION FORM

Safety Decal Serial Number _____

(Mounted on back halo of car)

Car Related Items

☐ Roll Cage
1" min clearance from top of driver's helmet to bottom of roll cage

☐ Seat/Shoulder Belts (2 yr., maximum, SFI, Anti-Sub) Exp. Date_____

☐ Nerf bars/Bumpers
Min. (3) 6/32 bolts, Grade 5 min. - Min. 3 bolts for nerfs includes shoulder bar

☐ Shoulder Bar
Min., 8/32 bolt at spud or clamp - Grade 5 min.

☐ Axles/Hubs
Axles not past wheels

☐ Belly Pan
Min., gauge 0.040 AL, no open holes

☐ Fire Wall
Min. Gauge 0.048 AL, no open holes

☐ Steering Wheel
1" thick, 2" diameter pad., min

☐ Steering
No over center, binds

☐ Ignition System *Fully Functional*

☐ Brakes
Metallic outer shield brake line

☐ Fuel System
Min.. of 2 hose clamps must be used if hose clamps are used. Ties and duct tape not permitted; min., 2 wraps of safety wire

☐ Fuel Line
Rated for Gasoline or Methanol

☐ Fuel Sleeve
Fire resistant sleeve

☐ Fuel Filter
Steel or Aluminum

☐ Check shut valve for leaks

☐ Vent hose end open & correct length
(see 2024 rule book)

☐ Exhaust system

☐ Throttle cable
(no binding)

☐ Tail cone
(below top of bumper)

☐ Tires/Wheels
(three lug nuts)

☐ Oil catch can
(Located under tail, only oil, not fuel)

☐ Weights
(Ballast cannot be mounted any higher than 7" above the bottom of lower frame rail. No ballast can be mounted to the body panels. Ballast can be mounted in the left side kick out but must be bolted to a metal kick out floor pan, a tab or a frame upright. Ballast in the kick out cannot be mounted to the side of the body panel or to a fiberglass floor. The kick out floor pan must be attached to the chassis with tabs, bolts or rivets, in order to attach any ballast. ALL weights attached through metal belly pans shall be secured with a min., 1.5" fender washer and bolts so that the bolt heads will not pull through the belly pans. Two (2) bolts are required if ballast is 6" or larger in length or width)

☐ Side Panels
L_____ R_____
(2" hole for access to flywheel nut; Max. 22" high, or easy nut access)

☐ Enclosed Nose Section

☐ NASCAR Youth Series Decal, Cookout Decal, Hoosier Decal

Driver Equipment

☐ **Helmet**
SA2020 or SA2025, FIA 8859-2015 or FIA 8859-2024, FIA 8860 valid 10 years from Date of Manufacture

☐ **Face Shield**
No cracks, SFI 3.2 A/1 min.

☐ **Neck Collar**
Nomex or Equivalent or Head & Neck Restraint SFI 38.1 Certified

☐ **Arm Restraints**
Worn close to wrist, not above elbow

☐ **Suit 1 or 2 piece**
SFI 3.2 A/1 min., no jeans; SFI 3.2 A/5 & head sock in Formula Mod

☐ **Shoes**
Completely cover feet, flat bottom

☐ **Gloves**
SFI 3.3/5, 1 layer

Effective January 1, 2012, Head and Neck Restraint Systems shall be inspected for recertification every five years after the date of original certification. Product inspection, maintenance, and/or replacement procedure is per individual manufacturer. Inspection must be done by the original manufacturer only, and not authorized resellers or dealers. When a unit is determined by the manufacturer to be acceptable for continued service and in compliance with the current version of the specification, the original manufacturer shall place on the product a new SFI 38.1 conformance label marked with the inspection date.

Driver's Name:_____ Handler's Name:_____

Safety Director Print/Sign : _____

Class:	Rookie	120	160	Form Mod	Animal	W/F
Division:		Junior	Senior	Light	Heavy	Unrestricted